

WEST



Generate Collection

L2: Entry 31 of 32

File: JPAB

Jun 15, 1993

PUB-NO: JP405148658A
DOCUMENT-IDENTIFIER: JP 05148658 A
TITLE: ELECTROLESS TIN PLATING METHOD

PUBN-DATE: June 15, 1993

INVENTOR-INFORMATION:

NAME

COUNTRY

TAKATSU, AKIO

NIHEI, TOMOMICHI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

SUMITOMO METAL MINING CO LTD

N/A

APPL-NO: JP03334454

APPL-DATE: November 22, 1991

US-CL-CURRENT: 427/304; 427/305

INT-CL (IPC): C23C 18/18; C23C 18/31; H01L 21/60; H05K 3/24

ABSTRACT:

PURPOSE: To enhance reliability in mounting a multi-pin TAB tape, etc., by treating the surface of a material to be plated with a liq. mixture of the acid, peroxide and org. high molecular compd. and then electroless-plating the material.

CONSTITUTION: Copper as a material to be plated is electroless-plated with tin. In this case, the surface of the material is treated with a liq. mixture of the acid, peroxide and org. high molecular compd., and then the material is electroless-plated. The plated material is further annealed. A soln. contg. at least one kind among sulfuric acid, hydrochloric acid, nitric acid and phosphoric acid is used as the acid. Ammonium persulfate or hydrogen peroxide is used as the peroxide. A compd. obtained by linking a straight-chain hydrocarbon or cyclic-carbon compd. to the sulfate-group or phosphate group or the salt of the compd. are used as the org. compd. Consequently, any trouble is hardly caused in the electric-component circuit.

COPYRIGHT: (C)1993, JPO&Japio